



**RIHM**  
GLOBAL SALES








**Rihm Global Sales**  
**POPULAR PARTS**

## AIR & BRAKE

RMC #:	REPLACES #:	DESCRIPTION:	PRODUCT INFORMATION:
109994RMC	109994	Air Dryer Cartridge (AD-SP, AD-IS, S51200, S51200P)	- 
3030-TSRMC	3030-TS	Springbrake, Type 30	Tandem Sealed (Complete) Includes Hardware & Clevis S-9137 
275491RMC	275491	Air Governor (D2)	All Ports 1/8" NPT Includes 4 Plugs & Mounting Gasket Pre-set at 125 PSI, New, No Core Charge 
BE 27157RMC	BE 27157	3 in 1 Air/Electric Hose Kit - 15'	Fully ABS Compatible, Spiral Wrapped for Clean Look Swivel End Fittings, Cold Weather Kink Resistant Large, Easy Grip Handles Color Coded for Gladhands Includes Hanger Bracket Mounting Assembly for Easy Suspension 
4707QRMC	4707Q	Brake Shoe Kit, Q Plus 16.5" X 7"	Meritor Q Plus Brake Systems New, No Core, NS301 LINING - COMPARABLE TO 23K & 312 LINING, Consists Of 2 Shoes & Hardware Kit Length: 16 1/2" (41.9cm), Width: 7" (17.8cm) Applications: Multiple Kenworth, Mack, Peterbilt & Volvo Applications 
800516RMC	800516	Control Valve (MV-3)	Replacement for Bendix MV-3™ Replacement for Midland Type 1 Plate (Recessed) Mounting Holes: 0.275" Open (No Threads) Ports: 1/4" NPT Applications: Multiple International, Freightliner, Kenworth & Volvo Applications 
R810019RMC	R810019	Clevis	5/8 Threads Works w/ Meritor Automatic Slack Adjusters 
275175RMC	275175	Control Valve (PP-1)	REPLACEMENT FOR BENDIX PP-1™ Delivery: (2) 1/8" NPT Supply: 1/8" NPT Exhaust: 1/8" Pop Pressure: 35-40 PSI Applications: Multiple International Applications 

## AIR & BRAKE

RMC #:	REPLACES #:	DESCRIPTION:	PRODUCT INFORMATION:	
1303RMC	1303	Brake Shoe Set, Emergency, Lined	10 x 3 DCM 5 Series Applications: International 4000 - 4400LP Series International 4600 - 4900 Series	
284358RMC	284358	Air Governor High Temp (D2)	Passed The SAE Standards Endurance Test 130 PSI Input Pressure & Delivery, Exhausted in a 4 Second Cycle +200,000 Times High Temperature All Ports 1/8 NPT Includes 4 Plugs & MTG. Gasket Pre-set at 125 PSI	
065706RMC	065706	Tractor Protection Valve (TP-3DC)	Replacement for Bendix TP-3DC™ Ports: 3/8 NPT Control, 1/4 & 1/2 NPT Stoplight Switch & Tractor Control R5 140/1/3/4/5	
R950068ARMC	R950068A	Air Dryer Cartridge, Oil Coalescing	-	
234101RMC	234101	Diaphragm, Type 30	Type: 30 Specially Formulated For Long Life & Hard Service Combination of Materials Insures Superior Strength, Flexibility & Resistance To Deterioration Operating Temperatures Range From -40° F To 212° F Directly Interchangeable w/ All Competitive Rubber & Neoprene Diaphragms	

## AIR & BRAKE

RMC #:	REPLACES #:	DESCRIPTION:	PRODUCT INFORMATION:	
BE1325ORMC	BE13250	Stop Light Switch	<p>Replacement For Haldex® Tractor Circuit Light Ports: 1/4 NPT Supply 3-5 PSI 2 Screw Terminals Sealed Non-Rebuildable Style</p>	
KN-47001RMC	KN-47001	Slack Adjuster, Manual, 5" - 6" - 7"	<p>Quantity Pack 6 Straight Arm Standard Duty W/ Bronze Bushings 30,000lb Rating W/ SAE J1461 Draft 4 Testing 30,000 in/lb Max. Spline: 10 Spline Diameter: 1-1/2" Arm Length: 5"-6"-7"</p>	
R801073RMC	R801073	Slack Adjuster, Automatic, 5.5", Meritor Style	<p>Meritor Style Stroke Sensing Non Quick-Connect Clevis Collar Lock Clevis 5.5 &amp; 6 Arms Complete W/ Straight Clevis Unhanded Design, Drilled Worm Wheel Factory Lubricated &amp; Sealed, Heavy Duty Internals No External Brackets Required Long Stroke Compatible, Finest Quality Ductile Nodular Iron Spline Length: 28 Spline Diameter: 1-1/2" Arm Length: 5-1/2"</p>	
AS1140RMC	AS1140	Slack Adjuster, Automatic, 5.5", Gunite Style	<p>Gunite Style Clearance Sensing Collar Lock Clevis 5.5 &amp; 6 Arms Complete W/ Straight Clevis Unhanded Design, Drilled Worm Wheel Factory Lubricated &amp; Sealed, Heavy Duty Internals No External Brackets Required Long Stroke Compatible, Finest Quality Ductile Nodular Iron Spline Length: 28 Spline Diameter: 1-1/2" Arm Length: 5-1/2"</p>	



## BEARINGS

RMC #:	REPLACES #:	DESCRIPTION:	PRODUCT INFORMATION:
5556503RMC	5556503	Cup & Cone Assembly	Multiple Applications
4304080RMC	4304080	Cylindrical Bearing	RTLO18718B, W/ Snap Ring Dimensions - Bore: 1.495", Outside Diameter - 3.2675" Multiple Applications



## BODY PARTS

RMC #:	REPLACES #:	DESCRIPTION:	PRODUCT INFORMATION:
FLT1900KITRMC	FLT1900KIT	Quarter Fender Set	Includes Left & Right Fenders & Clamp Dimensions: 24", High Impact Plastic Universal Applications
82329127RMC	82329127	Headlamp, RH	High Performance, Projection Style Lamp Slight Visual Difference from OEM, Recommended to Replace in Pairs, DOT / SAE compliant Plug and Play assembly, No programming required Made Of Impact Resistant Polycarbonate Lens Applications: Multiple Volvo Applications
82329124RMC	82329124	Headlamp, LH	High Performance, Projection Style Lamp Slight Visual Difference from OEM, Recommended to Replace in Pairs, DOT / SAE compliant Plug and Play assembly, No programming required Made Of Impact Resistant Polycarbonate Lens Applications: Multiple Volvo Applications
A21-28546-054RMC	A21-28546-054	Complete Bumper Assembly w/ Fog Lamp Holes	6 Piece Bumper, Color: Grey, Brackets 21-27302-000, Not Included Applications: Freightliner Cascadia (2008-2017)
20565618RMC	20565618	Hood Lock, LH	Applications: Volvo Applications LH: 2004 & Up, RH: 2004 & Before
T4695001RMC	T4695001	Windshield Washer Pump	Includes Grommet & Washer Bottle Applications: Multiple Peterbilt & Kenworth Applications, w/Grommet



## CLUTCH PARTS & COMPONENTS

RMC #:	REPLACES #:	DESCRIPTION:	PRODUCT INFORMATION:
23417527RMC	23417527	I Shift Clutch Actuator	Volvo I-Shift Clutch Actuator
85541RMC	85541	Clutch Brake	14" & 15 1/2" Clutches, Allen Screws To Secure/Close Inside Diameter: 2", Thickness: 0.380", 2.500"-2.570" Applications: Universal
06-01093RMC	06-01093	Clutch Release Shaft, 9.625"	Length: 9.625" Applications: Peterbilt 387 Model
127760RMC	127760	Torque Limiting Clutch Brake	14" & 15 1/2" Clutches, Torque Limiting, New Design Dim "A" - 2.500 - 2.570, Dimensions - 2" (0.380" Thick) 2.500"-2.570" Applications: Universal




## DRIVELINE REPLACEMENT PARTS

RMC #:	REPLACES #:	DESCRIPTION:	PRODUCT INFORMATION:
210661-1XRMC	210661-1X	Center Bearing	Dimensions - Bearing I.D (Max/Min):2.3622 / 2.3616 Height:3.38, Bearing Width: 1.41 Mounting Holes (Center-Center): 8.63" Applications: Freightliner Columbia 120 & Columbia (2007)
3-70-38XRMC	3-70-38X	Strap Kit	-
1810RMC	1810	Full Round Universal Joint	Applications: Volvo, International, Freightliner, Mack



## DRIVETRAIN

RMC #:	REPLACES #:	DESCRIPTION:	PRODUCT INFORMATION:
128634RMC	128634	Power Divider Case	Multiple Applications
127495RMC	127495	Drive Gear	Dana/Eaton DS404
A-6473RMC	A-6473	Oil Pump	Fuller FRO & FRLO Series




## DRIVETRAIN

RMC #:	REPLACES #:	DESCRIPTION:	PRODUCT INFORMATION:
KIT-5289RMC	KIT-5289	Synchronizer Kit	Meritor 9, 10 & 13 Speed
5-1659RMC	5-1659	Input Shaft	Multiple Applications
14373RMC	14373	Transmission Case Magnet	Applications: Fuller RTO, RTLO, RTLOF, FR, FRO & FROF Transmission Models
216220RMC	216220	Overhaul Kit	RD404/RD405 Rear Differential Overhaul Kit Applications: Dana/Eaton DS404
211468RMC	211468	Gear Set	Gear Set - 3.70 Teeth Count: 10/37 Applications: Replacement Dana Eaton DS344, DA404P, DS404P, DD404P, DS454P, DD454P, DA405P, DS405P, DD405P
127437RMC	127437	Axle Shaft	LENGTH: 41/64" Applications: Dana/Eaton DS404 & RS404, 210605
127438RMC	127438	Axle Shaft	LENGTH: 43-3/8" Applications: Dana/Eaton DS404 & RS404, 210605



## ELECTRICAL

RMC #:	REPLACES #:	DESCRIPTION:	PRODUCT INFORMATION:
3600-330-CRMC	3600-330-C	Relay	12 Volt Applications: International Prostar Linehaul Conventionals, International BE200, CE200, 300 & RE300 School Bus Series
POT/VF4-15F11RMC	POT/VF4-15F11	Micro Relay	5 Terminal, 10 Amp, 12 Volt Applications: Multiple Freightliner and Peterbilt Applications
20797838RMC	20797838	Turn Signal Switch	Applications: Volvo VHD Models (2005-2013) Volvo VN & VNL Models (2005-2012)
801538RMC	801538	ABS Speed Sensor - 75"	Replacement for Bendix® Body Type: 90° 75"/1905mm Connector Type: White Cannon
4410329212RMC	4410329212	ABS Speed Sensor - 15.75"	Replacement For WABCO® Body Type: 90° Connector Type: Black Cannon Length: 15.75" / 400mm Includes Wiring W/ Sensor Lube & 2 Half Moon Retainers



## ENGINE

RMC #:	REPLACES #:	DESCRIPTION:	PRODUCT INFORMATION:	
22303390RMC	22303390	Nitrogen Oxide (NOX) Sensor	Pre-Catalytic Sensor Applications: Volvo VN & VNL Models	
21577507RMC	21577507	DEF Pump	Mack MP7, 8, & 10 Engine Models Volvo D11, D13 & D16 Engine Models	
F31-6049RMC	F31-6049	Charge Air Cooler	Material - Aluminum & Aluminum Core Type: - Tube & Fin Dimensions - 33.50" x 30.08" x 2.00" Inlet/Outlet - 4.0"/4.0" Applications: Peterbilt 357, 379 & 385 Series (1995 & Up), Freightliner Conventionals (1995 & Up)	
1841-217-CRMC	1841-217-C	IPR Valve	International DT444E Engine Models Applications: International Amtran CE200/300 School Bus Series, International 3000FE, IC, RE School Bus Series (1999 & Up), International 3600 & 3800 School Bus Series (1997 & Up)	
13-03096RMC	13-03096	Radiator Mount	Flange 1/4" Nipple Applications: Freightliner Columbia & Century, Multiple Kenworth, Mack, & Peterbilt Applications	
FLF FRE1020 0001RMC	FLF FRE1020 0001	Charge Air Cooler Hose, Cold Air Return, 4"	Inside Diameter: 4" Length: 6.5" Cold Air Return	
22391563RMC	22391563	DEF Dosage Valve	Diesel Exhaust Fluid (DEF) Dosing Valve	



## EXHAUST

RMC #:	REPLACES #:	DESCRIPTION:	PRODUCT INFORMATION:	
EC50PLS-RRMC	EC50PLS-R	Exhaust Clamp, Stainless Steel	5" Stepped, Preformed, Stainless Steel Applications: International 9700 & 9800 Series Premium Cabovers Stainless Steel	
DDE A6809950302RMC	DDE A6809950302	Diesel Particulate Filter (DPF) Clamp, 10.5"	Nominal Diameter: 10.5"/ 267.66mm Coupler Width: 2.16"/55mm Stainless Steel Applications: Multiple Applications	
01-33035-000RMC	01-33035-000	Clamp-Constant Torque, 3.125"	SAE SIZE: 312, Min in: 2-1/2", Min mm: 57 Max in: 3-1/8", Max mm: 79, Applications: CT 300 L, CT 300 L 55, Heavy-duty construction for use on large diameter applications, 5/8" (15.8 mm) bandwidth Freightliner M2 106 (2012)	



## HVAC

RMC #:	REPLACES #:	DESCRIPTION:	PRODUCT INFORMATION:
X1987001RMC	X1987001	Cabin Air Filter	Filter only, no casing Dimensions - 8 15/16" x 7 7/8" x 1 3/16" Applications: Kenworth T680 Models Peterbilt 567 & 579 Series, International LT, 5900i
ABP N83 304543RMC	ABP N83 304543	A/C Compressor	8 Groove, Voltage: 12, Sanden Style 4417 Clutch Diameter: 4.7" (119 mm), Direct Mount 2 Wire Harness, Head Type: GH Refrigerant Type: R134A Applications: Freightliner Century, Columbia, M2, Cascadia & Coronado
85120276RMC	85120276	Blower Motor	12 Volt, 2 Wire, Assembly mount Double Shaft, Dimensions - 12.25" X 4 3/8" Shaft: 5/16" Applications: Multiple Volvo Applications



## PTO & HYDRAULICS



**BROAD RANGE OF  
OPTIONS AVAILABLE!**

## RADIATOR/CAC

RMC #:	REPLACES #:	DESCRIPTION:	PRODUCT INFORMATION:
A05-25263-005RMC	A05-25263-005	Surge Tank	Material: Plastic, Color: Clear Mount Hole Quantity : 4 Cap Maximum Pressure Rating : 15 PSI Includes Pressure Cap (05-20763-002), Filler Cap (BHT W3678001) & Coolant Sensor (06-62384-002) Applications: Freightliner Cascadia (2008-2019), Century (2008-2011), Columbia (2010-2015), Coronado (2010-2019), FLD120SD (2011), M2-106 (2014-2016), M2-112 (2008-2019)
3578-833-CRMC	3578-833-C	Surge Tank Cap	15 PSI Applications: International 9300, 9400, 9600, 9700 Series
N9267001RMC	N9267001	Fluid Level Sensor	Works w/ Surge Tank N5346001, Length: 4.48" Applications: Kenworth W900, T660 & T800 Models (2008 - 2019), Peterbilt 348, 335, 359, 365, 367, 377,379, 387, 382, 384, 385, 386, 388 & 389 Series (2008 - 2019)



## STEERING

RMC #:	REPLACES #:	DESCRIPTION:	PRODUCT INFORMATION:
14-14323-000RMC	14-14323-000	Power Steering Pump	2 Line Aluminum Pump CCW, 2 Bolt Flange, 11 Tooth Spline Shaft 4.25 USGPM Flow Rate, 2683 PSI, Aluminum Construction Applications: Freightliner Cascadia, Century, Coronado, FLD & M2



## SUSPENSION

RMC #:	REPLACES #:	DESCRIPTION:	PRODUCT INFORMATION:
KD2205RMC	KD2205	Leveling Valve	REPLACEMENT FOR BARKSDALE® Ports: 1/4" NPT, Includes Dump Feature Applications: Freightliern M2 106 (2012)
501-565-CRMC	501-565-C	Torque Rod Assembly	Length: 25.39" (Center to Center) Applications: International 3800 Series
1R12-069RMC	1R12-069	Air Spring	Extended Height: 21.10", Collapsed Height: 7.50" Applications: Peterbilt 330, 335, 337, 348, 357, 359, 377-379, 567, 579 & 587 Series
85989RMC	85989	Shock Absorber	Extended: 20.78", Compressed: 13.15" Applications: Kenworth K270, T270, T370, T680 & T880 Models, Peterbilt 348, 567 & 579 Series



## TRANSMISSION

RMC #:	REPLACES #:	DESCRIPTION:	PRODUCT INFORMATION:
K-2924RMC	K-2924	Basic Rebuild Kit	FR, 0 9, 11, 12, 13, 14, 15, 16, 17 & 18210 Electronic Applications: Fuller 9210 Thru 18210 Series w/ Electronic Speedometer
S-2822RMC	S-2822	Input Shaft	-
K-3492RMC	K-3492	Synchronizer Kit, Large Pin	Applications: Fuller 613, 910, 915, 6613, 9509, 9503, 11609, 12509, 12510, 12513, 12515, 14609, 14610, 14613, 14615



**ORDER PARTS TODAY!**  
**Parts@RihmGlobalSales.com**



Rihm Global Sales, a division of Rihm Family Companies is committed to offering original Kenworth trucks and spare parts to customers around the world with exceptional customer service and competitive pricing. Rihm Family Companies includes: Rihm Kenworth, Rihm Global Sales, RMC Truck Parts, and Rihm Leasing.



## CONTACT US

Phone: +1.651.646.7833  
Parts@RihmGlobalSales.com  
www.RihmGlobalSales.com

425 Concord Street South  
South St. Paul, MN 55075, USA